

TUBOFORM RM 90

Tube End Forming Machine with combined radial tooling (I/O)



Features / Equipment

- Electronic control with program storage
- Protective cover with safety switch
- User-friendly and easy to service
- High profitability due to short cycle times
- Mobile and flexible to use

Options

- Customer specific tooling
- Automatic loading and unloading system
- Electronic security systems
- Catch-pit for oil-spillage
- Counter for each work station

<p>Practical Applications</p>	
<p>Expanding, reducing, end sizing, bead forming, contour forming, ...</p>	

Technical Data	TUBOFORM RM 90
• Minimal tube diameter (for reducing)	20 mm
• Maximum tube diameter (for expanding)	74 mm
• Hydraulics	38 l/min, 150 bar
• Maximum forming force, internal tool	140 kN
• Maximum forming force, external tool	260 kN
• Number of work stations	1 - 2
• Dimensions (LxWxH)	1700 x 1000 x 1600 mm
• Weight, approx.	750 kg
• Operating voltage	400 V, 50 Hz, 3 phases
• Power requirement	8,0 kW

Subject to technical alteration • 2005-12



THE ONLY CHOICE FOR PERFECT PIPE INSTALLATIONS

TRACTO-TECHNIK GmbH & Co. KG Spezialmaschinen
 Hunold-Rump-Str. 76-80 · D-57368 Lennestadt
 Tel: +49 (0) 27 25 / 95 40 - 0 · Fax: +49 (0) 27 25 / 95 40 - 39
 www.tracto-technik.de · E-Mail: tubomat@tracto-technik.de