

TUBOFORM RS 8/13

Tube End Forming Machine with single radial tooling



Features / Equipment

- Electronic control with program storage
- Protective cover with safety switch
- User-friendly and easy to service
- High profitability due to short cycle times
- Mobile and flexible to use

Options

- Customer specific tooling
- Automatic loading and unloading system
- Electronic security systems
- Catch-pit for oil-spillage
- Counter for each work station



Technical Data	TUBOFORM RS 8	TUBOFORM RS 13
• Maximum tube diameter (for expanding)	130 mm	130 mm
• Minimal tube diameter (for reducing)	6 mm	6 mm
• Hydraulics	16 l/min, 160 bar	16 l/min, 230 bar
• Maximum forming force	80 kN	130 kN
• Horizontal travel of the slide	70 mm	70 mm
• Number of work stations	1 - 2	1 - 2
• Dimensions (LxWxH)	1700 x 1000 x 1600 mm	1700 x 1000 x 1600 mm
• Weight, approx.	500 kg	500 kg
• Operating voltage	400 V, 50 Hz, 3 phases	400 V, 50 Hz, 3 phases
• Power requirement	4 kW	5,5 kW

Subject to technical alteration • 2005-12



THE ONLY CHOICE FOR PERFECT PIPE INSTALLATIONS

TRACTO-TECHNIK GmbH & Co. KG Spezialmaschinen
 Hunold-Rump-Str. 76-80 · D-57368 Lennestadt
 Tel: +49 (0) 27 25 / 95 40 - 0 · Fax: +49 (0) 27 25 / 95 40 - 39
 www.tracto-technik.de · E-Mail: tubomat@tracto-technik.de