

VARIOMAT

Combined Tube Working Device for Cutting Ring Assembly and Flaring



VARIOMAT
with cutting ring assembly unit



VARIOMAT
with flaring unit

Features / Equipment

- Compact and rugged table-top unit for mobile and flexible use
- Very well suited for both, assembly of most cutting rings and flaring (37° SAE, 10°) of tubes with Ø 6 - 42 mm
- Manual pressure adjustment (according to clearly scheduled values) with digital display
- Integrated cooling for hydraulic oil
- Short cycle times of only few seconds
- Short set-up times when changing the tube diameter or the working method (between cutting ring assembly and flaring)



Regardless which connection method is favourite to you:

The VARIOMAT is the professional solution for both connections.

Options

- Storage box for cutting ring assembly tooling (assembling connections and counter-support plates)

Technical Data	VARIOMAT
• Tube diameter range	6 - 42 mm
• Hydraulics	3,7 l/min
• Capacity of hydraulic tank	3 l
• Maximum hydraulic pressure	200 bar
• Feed rate of the piston	6,9 mm/s
• Dimensions (WxHxD)	450 x 250 x 450 mm
• Weight, approx.	60 kg
• Operating voltage ¹	230 V, 50 Hz, 1 phase
• Power requirement	1,1 kW

¹ Other voltages on request

Subject to technical alteration • 2005-12



THE ONLY CHOICE FOR PERFECT PIPE INSTALLATIONS

TRACTO-TECHNIK GmbH & Co. KG Spezialmaschinen
 Hunold-Rump-Str. 76-80 · D-57368 Lennestadt
 Tel: +49 (0) 27 25 / 95 40 - 0 · Fax: +49 (0) 27 25 / 95 40 - 39
 www.tracto-technik.de · E-Mail: tubomat@tracto-technik.de